Ceres 686-2-4

Shown with Optional Bottom Blast Fan



Technical Specifications

Extreme Height
Extreme Width
Extreme Length
Width on Floor
Length on Floor
133"/338 cm
87"/224 cm
173"/437 cm
175"/182 cm
170"/432 cm

Capacities*

- Small Seed
- Medium Seed
- Large Seed & WheatMarket/Pre Cleaning

200-375 BPH (5.4-10.2 MT/Hr) 400-650 BPH (5.0-8.8 MT/Hr) 650-900 BPH (17.68-24.48 MT/Hr) 1200-2000 BPH (32.65-54. MT/Hr)

Electrical Requirements

Main Fan Motor
Eccentric Motor
Vibratory Feeder Motor
H.P./2.25 Kw
H.P./.375 Kw

Features

- Heavy Duty Construction Built to Last
- Uses Standard Clipper Screens
- Air Lock Trash Discharge Augers
- Front Door Holds in Screens
- Six Screen Decks 2 in Top Shoe & 4 in Bottom Shoe, 18 Screen Sections – 54" x 26"

Air Output 8,400 to 11,000 CFM

Options

- Bottom Blast Fan (Included in existing frame)
- Electronic Control Package
- Grease Line Package

Note: *Capacities may vary depending on seed condition, moisture content, seed varieties, types and volumes of contaminants to be separated and the percentage of foreign material acceptable in the final product.



835 - 58th Street East Saskatoon, SK, CAN, S7K 6X5 Tel: +1(306) 242-9292

Fax: +1(306) 934-4840 TOLL FREE: 1 (800) 667-6924

Mobile: +1(306) 222-6173